





PLT13 REWIRABLE PLUG

User Guide

⚠ PLEASE READ BEFORE USE



Do not drag adaptor along the track.



Do not leave adaptor "ON" when not in use.

Technical Specification

Product Description	: Rewirable Plug
Rated Voltage	: 250V a.c.
Rated Current	: 13Amp
Frequency	: 50Hz/60Hz
Fused	: 13Amp Fuse
Terminal Capacity	: 1.5mm ² (3 Core cable)
(Live, Neutral and Earth)	
Ambient Operating Temp.	: -5°C to +40°C (Not to exceed an average of more than 25°C in any 24 hours period)
Degree of Protection	: Ordinary
Material (Enclosure)	: Polycarbonate
Metal Components Material	: Brass, Phosphors Bronze
Weight	: Estimated 75 grams



Do not insert adaptor without aligning Locator to V-Groove.



Keep away from fire.



Keep away from water.




Not for outdoor use.




To be installed by a qualified electrician/installer.

User Instructions




Align Locator to V-Groove.
Push in plug.



Turn plug 90° clockwise.
(‘Click’ sound)



3



The plug is now switched on.
(LED indicator ‘ON’)

Wiring Instruction

Prepare leads as shown:



Live (Brown or Red)

Earth (Green or Green/Yellow)

Neutral (Blue or Black)

Cord Grip

Holster

FITTED WITH BS 1362 13A FUSE
ALWAYS FIT BS 1362 REPLACEMENT
CATRIDGE FUSE

3 Years Limited Warranty

1. Eubiq Pte Ltd (“Eubiq”) warrants to the end-user of the product (“the Customer”) that the product will be free from defects in materials and workmanship under normal use for a period of three (3) years from the date of retail purchase by the original end-user purchaser (“Warranty Period”).
2. The Customer should access and refer to Eubiq’s website at www.eubiq.com for a list of Eubiq authorised dealers to contact for warranty service.
3. All requests for warranty service must be made within the Warranty Period, and be accompanied by the original dated proof of purchase.

ALL RIGHTS RESERVED. EUBIQ AND GSS ARE THE REGISTERED TRADEMARKS OF EUBIQ PTE LTD.

www.eubiq.com